

SAFETY DATA SHEET

March 2010 Version 1.0

1. IDENTIFICATION OF PREPARATION AND OF COMPANY

Product Name:	Wickes CENTRAL HEATING JOINTING COMPOUND & EXTERNAL LEAK SEALER 50g Wickes SKU number: 221224
Application:	Domestic central heating systems
Identification of company:	KILROCK PRODUCTS LTD, UNIT 1B ALMA ROAD INDUSTRIAL ESTATE, CHESHAM, BUCKS HP5 3HB
Emergency contact:	Tel: 01494-793900 (office hours) Email: richard@kilrock.co.uk

2. INFORMATION ON INGREDIENTS

High Modulus Acetoxy Silicone Sealant

CAS NO	EC Number	DESIGNATION	CONC. (W/W)
017689-77-9	241-677-4	Triacetoxyethylsilane	<5%
004253-34-3	224-221-9	Methylsilanetriyl triacetate	<1%

Product contains Acetic Acid CAS NO 64-19-7 EC No 200-580-7 at <10% which is below the concentration limit that would have otherwise required the Xi symbol and R36/38 risk phrases "Irritating to eyes and skin".

3. HAZARDS IDENTIFICATION

The cured product is generally not irritating to the skin. However, as a general precaution, avoid prolonged contact with uncured product and use in well ventilated areas.

4. FIRST-AID MEASURES

Ingestion:	Rinse mouth with water and seek medical advice.
Skin contact:	Remove with dry cloth, then wash with detergent and water.
Inhalation:	Move person to fresh air.
Eyes:	Rinse for 15 minutes with plenty of water. Seek medical attention if irritation persists.

5. FIRE FIGHTING MEASURES

Suitable extinguishing media Water fog, carbon dioxide and dry powder.
Special exposure hazards None known.
Special equipment for firefighters Self contained breathing apparatus is required.

6. ACCIDENTAL RELEASE MEASURES

Scrape up and place in a container with a lid. The spilled product produces an extremely slippery surface.

7. HANDLING AND STORAGE

Keep container closed when not in use. Avoid contact with skin and eyes. Store in a cool, dry place. Store below 30°C. Product releases acetic acid during application and curing.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hand protection Cloth gloves.
Eye protection Safety glasses.

Use only in well-ventilated areas.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Paste
Colour Clear
Odour Pungent acidic
Solubility in water Insoluble
Hardness 15 Shore A
Temperature resistance -40 to +200°C

10. STABILITY AND REACTIVITY

If stored and handled in accordance with standard industrial practices no hazardous reactions are known.

11. TOXICOLOGICAL INFORMATION

Acetic acid is released during curing. Prolonged or repeated contact may cause transient irritation to eyes.

After curing, product is not hazardous to man.

12. ECOLOGICAL INFORMATION

The product is not classified as dangerous for the environment.

13. DISPOSAL CONSIDERATIONS

Dispose in accordance with local regulations. Spent tube is aluminium and may be recycled.

14. TRANSPORT INFORMATION

Non-hazardous
Airmail/Land express: Permitted.

15. REGULATORY INFORMATION

EC Labelling None
Risk Phrases None
Safety Phrases None

Use label Information:

- Keep out of reach of children
- Avoid contact with skin and eyes
- Use only in well ventilated areas

16. OTHER INFORMATION